





70 CFM/1.5 Sones @ 0.10" SP., 32.2 Watts 57 CFM @ 0.25" SP.

Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10° x 10° .

Blower Wheel

One piece polymeric wheel 51/8" diameter, 23/8" wide, with 48 fins.

Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz.

Fan Housing

PC/ABS polymeric, dimensions 81/2" x 91/8" x 43/4".

Duct Collar


Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area

For bathrooms up to 65 sq. ft. For other rooms up to 85 sq. ft.

Single Pack Shipping Info

Box Dim: 11" x 12" x 6" UPC: 0-8316227501-1 Shipping Weight: 5¹/₄ lbs.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.





Unit Mounting

Rated for ceilings insulated to R-40. Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to $^{3/4}$ ", with a rough-in opening of $8^{1/2}$ " x $9^{1/8}$ ".

Suitable for wall insert mounting when discharged vertically and mounted outside of shower enclosure

EXPANDED PERFORMANCE														
									HVI Sones	HVI Sones	HVI Sones	Fan Speed	Power	
	Static Pressure (inches of w.g.))	@ .1 SP	@ .25 SP	@.30 SP	RPM	Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25	0.3						
Air Flow - CFM	79	74	70	68	66	62	57	50	1.5	2.0	3.0	1300	32.2	0.3

PROJECT								ARCHITECT				
LOCATION								ENGINEER				
CONTRACTOR								SUBMITTED BY DATE				
FAN Number	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS			

Fax: (610) 696-8048





U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 ● 877-304-3785 **Canada:** 8 Edvac Drive Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 Fax: (905) 456-1015

Specifications subject to change without notice.