



GEMINI

ZERO CLEARANCE DIRECT VENT SEE THROUGH GAS FIREPLACE

## WALL SURROUND

FLATT

BLACK

PEWTER

# STYLING



SPLIT OAK LOG SE



**ROCK COLLECTION** 



Model	MDVL31N MDVR31N	MDVL39N <sup>†</sup> MDVR39N <sup>†</sup>	MDVL31LP MDVR31LP
	MICAAOIM	MDAKSAN	MDAKSIFL
Fuel	Natural	Natural	Propane
Input Max.	30,000 BTU	39,000 BTU	30,000 BTU
Glass Type	Tempered	Ceramic	Tempered
Certification	Decorative	Decorative	Decorative
<b>Bedroom Approved</b>	*Yes	*Yes	*Yes
FE (P.4.1-02)	57.7%	56.6%	54.7%

 $<sup>^{*}</sup>$ Must be installed with listed thermostat in Canada. Check local jurisdiction in USA.

### STANDARD FEATURES\*

- > Millivolt or IPI valve system allows operation during a power failure with Hi/low heat and flame adjustment
- > A triple burner for use with our contemporary rock collection or log set.

### **OPTIONAL FEATURES**

Designer Clean View Circulating Kit – No Louvers Required. (Available as See Through only, see manual for framing instructions – Model MDV31 only)

Grills - Black, Classic Series - Antique Brass, Chrome and Polish Brass

Surrounds – (Louvered, See Through only) – Black, Antique, Polish Brass, Chrome

Overlay Doors - (Large Glass Panel Only) Deluxe, Top Half

Designer Doors – (Large Glass Panel Only) Arch or Straight Black Doors

Fan Kit – Heat activated with variable speed control

Brick Refractory Liners – End Panel, Side Panel

Thermostat\* – Wall Mount Millivolt Thermostat or Programmable Thermostat

Remote Control - On/Off, Thermostat\*,

Thermostat\*/Modulating or Thermostat\*/Modulating Fan

### Child Safety Screen

Wall Surrounds Flatt – with Black or Pewter finishes (For use with Z36CVCK only)

#### Wall Surrounds Flatt Accents

- > Keystone Brushed Chrome or Black
- > Designer Band Accents 4 x Black (sml), 2 x Chrome (Irg)
- > Designer Corner Accents 4 x Black

### Log Set or Contemporary Rock Collection

\*Thermostats are not permitted on Decorative Appliances (ANSI Z21.50) in the USA






Top Flue Model	He	Height		Front Width		Depth	
	Actual	Framing	Actual	Framing	Actual	Framing	
LOUVERS							
Corner	361/8"	37"	381/6"	415/8"	2111/16"	271/4"	
Pennisula	361/8"	37"	381/6"	41 <sup>5</sup> /8"	2111/16"	20 <sup>5</sup> /8"	
See Thru	361/8"	37"	411/16"	411/8"	2111/16"	20 <sup>5</sup> /8"	
CLEAN VIEW CIRCULATING KIT (CVCK)							
See Thru	<b>41</b> <sup>5</sup> /8"	421/2"	381/8"	461/8"	26 <sup>5</sup> /8"	25 <sup>5</sup> /8"	

Consult Manual for proper framing instructions in order to meet clearances to combustibles.

MQSW Wall Mount Surround Dimensions (inches)



Louvered model only.





Kingsman Fireplaces maintains a program of continuous testing, refinement and improvemen of all its products. Some aspect of units shown here may be changed at any time without notice of the continuous proceduration.

Certification: The models are certified for USA and Canac Certified to: ANSI Z21.50b-2009, CSA 2.22b-2009, CGA 2.17-M91 as a Vented Gas Fireplac

ordered separately to create a complete unit.

th your local Kingsman dealer for clarification

400