





70 CFM/1.5 Sones @ 0.10" SP., 32.2 Watts 57 CFM @ 0.25" SP.

Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10° x 10° .

Blower Wheel

One piece polymeric wheel 51/8" diameter, 23/8" wide, with 48 fins.

Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz.

Fan Housing

PC/ABS polymeric, dimensions 81/2" x 91/8" x 43/4".

Duct Collar


Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area

For bathrooms up to 65 sq. ft. For other rooms up to 85 sq. ft.

Single Pack Shipping Info

Box Dim: 11" x 12" x 6" UPC: 0-8316227501-1 Shipping Weight: $5^{1/4}$ lbs.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.





• Unit Mounting

Rated for ceilings insulated to R-40. Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to $^{3/4}$ ", with a rough-in opening of $8^{1/2}$ " x $9^{1/8}$ ".

Suitable for wall insert mounting when discharged vertically and mounted outside of shower enclosure

EXPANDED PERFORMANCE														
									HVI Sones	HVI Sones	HVI Sones	Fan Speed	Power	
	Static Pressure (inches of w.g.))	@ .1 SP	@ .25 SP	@.30 SP	RPM	Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25	0.3						
Air Flow - CFM	79	74	70	68	66	62	57	50	1.5	2.0	3.0	1300	32.2	0.3

PROJECT								ARCHITECT				
LOCATION								ENGINEER				
CONTRACTOR							SUBMITTED BY DATE					
FAN NUMBER N	MODEL Number	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS			





U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 ● 877-304-3785

Fax: (610) 696-8048

Canada: 8 Edvac Drive Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 Fax: (905) 456-1015